

GAALFLEX® CHAIN T 87 C LEAN

Continuously flexible PVC control cable with overall copper screen, DIN VDE 300/500 V UL/CSA 600 V






ELETTROTEK KABEL® GAALFLEX® CHAIN T 87 C Lean



Construction:

CONDUCTOR:	FLEXIBLE RED COPPER CONDUCTOR CL. 6, ACC TO IEC 60228, DIN VDE 0295
INSULATION:	PVC COMPOUND
COLOUR CORES:	BLACK CORES WITH CONSECUTIVE NUMBERS ACC. TO EN 50334, GREEN-YELLOW FROM 3 CORES
STRANDING:	IN LAYERS
WRAPPING:	NON WOVEN TAPE OVER EACH LAYER
SCREEN:	TINNED COPPER BRAID
WRAPPING:	NON-WOVEN TAPE
OUTER SHEATH:	GREY (RAL 7000 OR 7001), PVC COMPOUND

Resistance:

	SELF-EXTINGUISHING AND FLAME RETARDANT ACC. TO: DIN VDE 0482 PART 265-2-1 EN 50265-2-1 IEC 60332-1-2 IEC 60332-3-24 UL VW-1, CSA FT1
	OIL RESISTANCE ACC. TO: DIN EN 50290-2-22 TM 54
	UV RESISTANT / SUNLIGHT RESISTANT: ACC. TO ISO 4892-3

Technical data:

NOMINAL VOLTAGE:	DIN VDE: U0/U 300/500 V UL: 600 V
TEST VOLTAGE:	3 KV ACC. TO DIN VDE 0281 PART 2 + HD 21.2
TEMPERATURE RANGE	DIN VDE: UL/CSA:
<i>FIXED LAYING:</i>	-30°C UP TO +80°C UP TO +90°C
<i>FLEXIBLE INSTALLATION:</i>	-0°C UP TO +80°C
RADIATION RESISTANCE:	8 X 10 ⁻⁷ Cj/Kg
MIN. BENDING RADIUS	
<i>CONTINUOUSLY FLEXIBLE:</i>	8 x D
MAX SPEED (MAIN APPLICATION):	180 mt/min

Features:

- AWM STYLE 2587 90°C 600V
CSA AWM I/II A/B 90°C 600V FT1 CE
- VERY GOOD FLEXIBILITY
- SMALL OUTER DIAMETER
- SMALL BENDING RADIUS
- GOOD EMC CHARACTERISTICS
- ROHS AND CE APPROVAL




GAALFLEX® CHAIN T 87 C LEAN

Continuously flexible PVC control cable with overall copper screen, DIN VDE 300/500 V UL/CSA 600 V



ELETTROTEK KABEL® GAALFLEX® CHAIN T 87 C Lean



Part no.	No. of cores x cross section n x mm ²	Outer-Ø ca. mm ± 10%	Copper weight kg/km	Cable weight approx. kg/km	AWG no. *)
36110F41020A20	2 X 0,5	5,7	27	50	20
36110F40031A20	3 G 0,5	6,2	32	60	20
36110F40041A20	4 G 0,5	6,6	42	75	20
36110F40051A20	5 G 0,5	7,1	47	85	20
36110F40071A20	7 G 0,5	8,5	62	115	20
36110F40121A20	12 G 0,5	10,1	92	165	20
36110F40181A20	18 G 0,5	11,8	132	230	20
36110F40251A20	25 G 0,5	14,4	190	330	20
36110F41020A19	2 X 0,75	6,2	32	60	19
36110F40031A19	3 G 0,75	6,7	44	75	19
36110F40041A19	4 G 0,75	7,2	52	90	19
36110F40051A19	5 G 0,75	7,8	64	105	19
36110F40071A19	7 G 0,75	9,5	84	150	19
36110F40121A19	12 G 0,75	11,3	126	215	19
36110F40181A19	18 G 0,75	13,3	181	300	19
36110F40251A19	25 G 0,75	16,1	260	430	19
36110F41020A18	2 X 1	6,4	42	70	18
36110F40031A18	3 G 1	7	51	85	18
36110F40041A18	4 G 1	7,4	61	100	18
36110F40051A18	5 G 1	8,3	76	125	18
36110F40071A18	7 G 1	9,9	101	165	18
36110F40121A18	12 G 1	11,8	160	250	18
36110F40181A18	18 G 1	14,2	243	370	18
36110F40251A18	25 G 1	17	320	500	18
36110F41020A16	2 X 1,5	7	51	85	16
36110F40031A16	3 G 1,5	7,6	72	105	16
36110F40041A16	4 G 1,5	8,4	86	135	16
36110F40051A16	5 G 1,5	9,1	106	160	16
36110F40071A16	7 G 1,5	11,1	140	220	16
36110F40121A16	12 G 1,5	13,2	224	330	16
36110F40181A16	18 G 1,5	15,9	340	490	16
36110F40251A16	25 G 1,5	19	461	670	16
36110F41020A14	2 X 2,5	8,9	89	140	14
36110F40031A14	3 G 2,5	9,2	106	155	14
36110F40041A14	4 G 2,5	10,1	130	195	14
36110F40051A14	5 G 2,5	11,2	160	235	14
36110F40071A14	7 G 2,5	13,3	219	325	14
36110F40121A14	12 G 2,5	16,4	369	520	14
36110F40181A14	18 G 2,5	18,1	517	690	14
36110F40251A14	25 G 2,5	21,7	706	915	14
36110F40031A12	3 G 4	10,7	165	235	12
36110F40041A12	4 G 4	11,8	199	280	12
36110F40051A12	5 G 4	13,2	243	340	12
36110F40031A10	3 G 6	13,4	220	355	10
36110F40041A10	4 G 6	14,5	301	425	10
36110F40051A10	5 G 6	16,2	369	515	10
36110F40041A08	4 G 10	18,6	475	670	8
36110F40051A08	5 G 10	19,2	588	820	8
36110F40041A06	4 G 16	21,7	725	980	6
36110F40051A06	5 G 16	22,4	860	1210	6
36110F40041A04	4 G 25	24	1040	1515	4
36110F40051A04	5 G 25	27,7	1290	1790	4
36110F40041A02	4 G 35	27	1415	1910	2
36110F40041A01	4 G 50	28,1	1970	2715	1

Other dimension and colours available on request.