

GAALSHIP® HF 250 OS FR WSR

Pairs/triples twisted cables telecommunication and instrumentation cable, overall screened, fire resistant and water spray resistant



ELETTROTEK KABEL® GAALSHIP® HF 250 OS FR WSR

Applications:

Fire resistant and water spray instrumentation cables for fixed electrical installations aboard ships, screened against electromagnetic interferences, suitable for the signal and telecommunication of safety-fire devices. These cables prevent the cable short-circuit due to water sprays of Fire Fighters' hydrants used during the fire, allowing the continuous operation of these devices.

Construction:

Conductor:	Plain annealed copper or Tinned annealed copper conductor Cl. 2, acc. to IEC 60228, DIN VDE 0295
Insulation:	MICA glass tape + GAALTHERM® 597
Cores color:	Pair: black- light blue Triple: black- light blue - brown
Stranding:	Core laid-up together in pairs/triples
Overall screen:	Aluminium/polyester tape with tinned annealed copper stranded drain wire
1st Wrapping:	Glass fiber tape
2nd Wrapping:	Two plain annealed copper / polyester tapes
3rd Wrapping:	Glass fiber tape
Outer sheath:	Halogen free thermoplastic compound SHF1 acc. to IEC 60092-360, thickness acc. to IEC 60092-376
Marking:	ELETTROTEK KABEL® GAALSHIP® HF 250 OS FR WSR, cross nominal section sqmm, 150/250 V, part n°, IEC 60092-376, IEC 60332-3-22, IEC 60331, BS 8491, production plant, batch n°, production date, CE RoHS, progressive meter marking.

Technical data:

Nominal voltage:	150/250 V
Temperature range:	-40°C up to +90°C
Installation temp.:	-5°C
Short circuit temperature:	+250°C
Min. bending radius:	4 x Outer diameter

Type Approvals/Certificates:

RINA / RINAMIL (Registro Italiano Navale)
BV (Bureau Veritas)
LR (Lloyd's Register)
DNV-GL (Det Norske Veritas - Germanischer Lloyd)
ABS (American Bureau of Shipping)
RMRS (Russian Maritime Register of Shipping)
Other approvals on request

Resistance:



Fire resistant acc. to:
IEC 60331-21,
IEC 60331-2 (under 20 mm Ø),
IEC 60331-1 (over 20 mm Ø),
EN 50200 Annex E Water Spray Test,
BS 8491 Water Jet Test



Flame and fire retardant acc. to:
IEC 60332-1-2,
IEC 60332-3-22



Halogen free acc. to:
IEC 60754-1/2



Smoke emission properties acc. to:
IEC 61034-1/2

Features:

Sheathing and insulating materials acc. to IEC 60092-360
Design guidelines acc. to IEC 60092-350/376
Choice and installation of electric cables acc. to IEC 60092-352
Cold bend test at low temperatures
acc. to CSA C22.2 No. 0.3-09 (-40°C)
Cold bend impact at low temperatures
acc. to CSA C22.2 No. 0.3-09 (-35°C)
On request class 5 conductor acc. to IEC 60228

GAALSHIP® HF 250 OS FR WSR

Pairs/triples twisted cables telecommunication and instrumentation cable, overall screened, fire resistant and water spray resistant



ELETTROTEK KABEL® GAALSHIP® HF 250 OS FR WSR



Part no.	No. of pairs/triples x cross section n x mm ²	Outer sheath color	Outer diameter ca.mm			Cable weight approx. kg/km	Max. resistance of conductors at 20°C (Ohm/km)	Current rating in open air at 45°C (A)	Short circuit rating I sec. (kA)
			Min.	Nom.	Max.				
11200CGX052M05	5 x 2 x 0,5	Orange	16,8	18,3	19,8	348	41,6	5	0,07
11200CGX012M07	1 x 2 x 0,75	Orange	9,1	10,6	12,1	138	26,3	12	0,11
11200CGX022M07	2 x 2 x 0,75	Orange	10,7	12,2	13,7	178	26,3	10	0,11
11200CGX042M07	4 x 2 x 0,75	Orange	16,1	17,6	19,1	323	26,3	7	0,11
11200CGX052M07	5 x 2 x 0,75	Orange	17,6	19,1	20,6	388	26,3	7	0,11
11200CGX072M07	7 x 2 x 0,75	Orange	18,9	20,9	22,4	455	26,3	7	0,11
11200CGX102M07	10 x 2 x 0,75	Orange	23,5	25,5	27	673	26,3	7	0,11
11200CGX142M07	14 x 2 x 0,75	Orange	26,5	29	31,5	821	26,3	6	0,11
11200CGX242M07	24 x 2 x 0,75	Orange	34,4	36,9	39,4	1327	26,3	5	0,11
11200CGX372M07	37 x 2 x 0,75	Orange	41,4	43,9	46,4	1851	26,3	5	0,11
11200CGX012M10	1 x 2 x 1	Orange	9,5	11	12,5	152	19,3	15	0,14
11200CGX032M10	3 x 2 x 1	Orange	15,3	16,8	18,3	296	19,3	10	0,14
11200CGX042M10	4 x 2 x 1	Orange	16,8	18,3	19,8	360	19,3	8	0,14
11200CGX072M10	7 x 2 x 1	Orange	19,8	21,8	23,3	513	19,3	8	0,14
11200CGX012M15	1 x 2 x 1,5	Orange	10,6	12,1	13,6	186	12,9	19	0,21
11200CGX022M15	2 x 2 x 1,5	Orange	12,4	13,9	15,4	246	12,9	16	0,21
11200CGX042M15	4 x 2 x 1,5	Orange	18,9	20,4	21,9	452	12,9	11	0,21
11200CGX052M15	5 x 2 x 1,5	Orange	20,9	22,4	23,9	561	12,9	11	0,21
11200CGX072M15	7 x 2 x 1,5	Orange	22,3	24,3	25,8	654	12,9	11	0,21
11200CGX072M15	8 x 2 x 1,5	Orange	26,6	28,6	30,1	799	12,9	11	0,21
11200CGX102M15	10 x 2 x 1,5	Orange	27,8	29,8	31,3	970	12,9	11	0,21
11200CGX122M15	12 x 2 x 1,5	Orange	29,8	32,3	34,8	1059	12,9	11	0,21
11200CGX192M15	19 x 2 x 1,5	Orange	35,7	38,2	40,7	1554	12,9	9	0,21
11200CGX012M25	1 x 2 x 2,5	Orange	11,5	13	14,5	223	8,0	27	0,36
11200CGX013M07	1 x 3 x 0,75	Orange	9,8	11,3	12,8	153	26,3	10	0,11
11200CGX073M07	7 x 3 x 0,75	Orange	21,9	23,4	25,4	606	26,3	7	0,11
11200CGX073M10	7 x 3 x 1	Orange	22,9	24,4	26,4	688	19,3	8	0,14

Other dimensions and colors available on request.