


GAALFLEX® TRAY INSTRUMENTATION 600 TOS PVC

Special triads PVC-Nylon/PVC UV and oil resistant, with overall Aluminium tape screen, TC-ER 90°C 600V Dry or wet, UL 1277 type TC



ELETTROTEK KABEL® GAALFLEX® INSTRUMENTATION 600 TOS PVC



Construction:

Conductor:	Stranded red copper, acc.to ASTM B-3, Class B and ASTM B-8
Insulation:	special PVC/Nylon type TFN acc. to UL 66, flame-retardant 90°C
Colour cores:	acc. to ICEA table E1: traids: black, white and red numbered
Stranding:	in triads
Screen:	aluminium tape + PETP foil, + tinned copper drain wire
Ripcord:	nylon ripcord under outer sheath
Outer sheath:	black (RAL 9005), special PVC compound, flame retardant and UV resistance

Technical data:

Nominal voltage UL:	600 V
Test voltage:	4 kV
Temperature range UL:	
<i>Dry:</i>	up to +90°C
<i>Wet:</i>	up to +75°C
Min. bending radius:	
<i>Fixed laying:</i>	5 x d
<i>During Installation:</i>	8 x d

Resistance:



Fire performance acc. to:
UL 1685 / IEEE 383
vertical fire test at 70.000 BTU/hr

Features:

cable for tray use
outdoor use
sunlight moisture and weather resistance
oil and gasoline resistance due to PVC/Nylon insulation
DIRECT BURIAL
LEAD FREE
suitable for use in cable trays, raceways, conduit or for aerial applications where installed with a messenger
type TC acc. to NEC 2008 and NEC 2011 Article 336
suitable in class I Division 2 and Class 2 Division 2 Hazardous Locations and intrinsically safe application acc. to NEC 2008 and NEC 2011 articles 392, 501, 502, 503, 505
suitable in class 1 circuits, acc. to NEC 2008 and NEC 2011 articles 336.10 and 725 for type TC cables
suitable for nonpower-limited alarm circuits acc. to NEC 2008 and NEC 2011 articles 336.10 and 760.46
on request tinned copper conductors
on request welded and corrugated aluminium armor and PVC outer sheath
on request interlocked aluminium armour with or without PVC outer sheath
on request RoHS and CE approval



UL Standards

TC: UL Standard 1277 Dry or Wet 90°C 600 V
UL 66: fixture for 18/16 AWG, type TFN 90°C 600 V


DATA AND INSTRUMENTATION CABLES

GAALFLEX® TRAY INSTRUMENTATION 600 TOS PVC

Special triads PVC-Nylon/PVC UV and oil resistant, with overall Aluminium tape screen, TC-ER 90°C 600V Dry or wet, UL 1277 type TC



ELETTROTEK KABEL® GAALFLEX® INSTRUMENTATION 600 TOS PVC



Part no.	No. of triad(s) x cross section n x AWG	Outer-Ø Inches/mm ± 10%	Copper weight Lbs/Mft - kg/km	Cable weight approx. Lbs/Mft - kg/km
32161F7K013A18	1 x 3 x 18	0,283 - 7,19	-	51 - 76
32161F7K023A18	2 x 3 x 18	0,442 - 11,23	-	90 - 134
32161F7K043A18	4 x 3 x 18	0,513 - 13,03	-	153 - 228
32161F7K083A18	8 x 3 x 18	0,700 - 17,78	-	282 - 420
32161F7K103A18	10 x 3 x 18	0,820 - 20,83	-	345 - 513
32161F7K123A18	12 x 3 x 18	0,886 - 22,50	-	427 - 635
32161F7K163A18	16 x 3 x 18	0,982 - 24,94	-	538 - 801
32161F7K203A18	20 x 3 x 18	1,088 - 27,64	-	651 - 969
32161F7K243A18	24 x 3 x 18	1,208 - 30,68	-	765 - 1138
32161F7K363A18	36 x 3 x 18	1,382 - 35,10	-	1080 - 1607
32161F7K503A18	50 x 3 x 18	1,628 - 41,35	-	1451 - 2159
32161F7K013A16	1 x 3 x 16	0,309 - 7,85	-	68 - 101
32161F7K023A16	2 x 3 x 16	0,490 - 12,45	-	120 - 179
32161F7K043A16	4 x 3 x 16	0,601 - 15,27	-	222 - 330
32161F7K083A16	8 x 3 x 16	0,779 - 19,79	-	383 - 570
32161F7K103A16	10 x 3 x 16	0,955 - 24,26	-	503 - 749
32161F7K123A16	12 x 3 x 16	0,985 - 25,02	-	578 - 860
32161F7K163A16	16 x 3 x 16	1,094 - 27,79	-	735 - 1094
32161F7K203A16	20 x 3 x 16	1,214 - 30,84	-	893 - 1329
32161F7K243A16	24 x 3 x 16	1,351 - 34,32	-	1055 - 1570
32161F7K363A16	36 x 3 x 16	1,549 - 39,34	-	1505 - 2240
32161F7K503A16	50 x 3 x 16	1,887 - 47,93	-	2142 - 3188
32161F7K013A14	1 x 3 x 14	0,336 - 8,53	-	91 - 135

Other dimensions and colors available on request.