


FESTOON CABLES

FLEXIFESTOON® SOOW

EPDM/CPE cable, UL 600 V -40°C up to 90°C - CSA SOOW 600 V -40°C up to +90°C FT2 Water resistant, MSHA



ELETTROTEKKABEL® FLEXIFESTOON® SOOW
UL 600 V -40°C up to 90°C - CSA SOOW 600 V
-40°C up to 90°C FT2 Water resistant, MSHA



Construction:

Conductor:	finely stranded red copper acc.to Cl. K, acc. to ASTM B-174
Insulation:	rubber EPDM compound
Cores color:	acc. to ICEA Method 1-E1 (K-1)
Stranding:	in layers
Outer sheath:	black (similar to RAL 9005), rubber CPE compound

Resistance:



Flame test acc. to:
CSA FT 2

Technical data:

Nominal voltage:	600 V
Test voltage:	2 kV
Temperature range:	
<i>Fixed laying:</i>	-40°C up to +90°C
<i>Flexible application:</i>	-40°C up to +90°C
Min. bending radius:	
<i>Fixed laying:</i>	4 x D
<i>Flexible application:</i>	4 x D

Features:

UV, ozone, water, oil and abrasion resistant

flexible in cold weather

on request tinned copper conductor

on request screened version

(UL) 600 V -40°C up to 90°C
CSA 600 V -40°C up to 90°C FT2

acc. to UL standard 62

acc. to CSA 22.2 No. 49

acc. to NEC 501.140 Class I, Division. 1 and 2

acc. to NEC Article 400

MSHA approval

RoHS approval



FESTOON CABLES

FLEXIFESTOON® SOOW

EPDM/CPE cable, UL 600 V -40°C up to 90°C - CSA SOOW 600 V -40°C up to +90°C FT2 Water resistant, MSHA



ELETTROTEKKABEL® FLEXIFESTOON® SOOW
UL 600 V -40°C up to 90°C - CSA SOOW 600 V
-40°C up to 90°C FT2 Water resistant, MSHA



Part no.	No. of cores x cross section n x AWG	Outer-Ø inches/mm ± 10%	Cable weight approx. Lbs/Mft-kg/km	Current capacity at +30°C Amps
03200F7K020A18	2 x 18	0,346 - 7,6	67 - 100	10
03200F7K030A18	3 x 18	0,365 - 9,27	84 - 125	10
03200F7K040A18	4 x 18	0,39 - 9,91	98 - 146	7
03200F7K050A18	5 x 18	0,465 - 11,81	116 - 173	5
03200F7K020A16	2 x 16	0,37 - 9,4	81 - 121	13
03200F7K030A16	3 x 16	0,39 - 9,91	94 - 140	13
03200F7K040A16	4 x 16	0,415 - 10,54	118 - 176	10
03200F7K050A16	5 x 16	0,495 - 12,57	143 - 213	8
03200F7K080A16	8 x 16	0,575 - 14,6	222 - 331	-
03200F7K100A16	10 x 16	0,62 - 15,8	278 - 414	-
03200F7K120A16	12 x 16	0,66 - 16,8	305 - 454	-
03200F7K020A14	2 x 14	0,5 - 12,7	134 - 199	18
03200F7K030A14	3 x 14	0,525 - 13,34	169 - 252	18
03200F7K040A14	4 x 14	0,57 - 14,48	201 - 299	15
03200F7K050A14	5 x 14	0,668 - 16,97	272 - 405	12
03200F7K080A14	8 x 14	0,74 - 18,9	324 - 480	32
03200F7K020A12	2 x 12	0,57 - 14,48	184 - 274	25
03200F7K030A12	3 x 12	0,595 - 15,11	224 - 333	25
03200F7K040A12	4 x 12	0,650 - 16,51	276 - 411	20
03200F7K050A12	5 x 12	0,713 - 18,11	318 - 473	16
03200F7K080A12	8 x 12	0,80 - 20,2	408 - 607	14
03200F7K200A12	20 x 12	1,22 - 31	971 - 1445	10
03200F7K020A10	2 x 10	0,615 - 15,62	225 - 335	30
03200F7K030A10	3 x 10	0,66 - 16,76	299 - 445	30
03200F7K040A10	4 x 10	0,71 - 18,03	360 - 536	25
03200F7K050A10	5 x 10	0,77 - 19,56	409 - 609	20
03200F7K030A08	3 x 8	0,88 - 22,35	485 - 722	40
03200F7K040A08	4 x 8	0,953 - 24,21	619 - 921	35
03200F7K050A08	5 x 8	1,034 - 26,26	722 - 1074	28
03200F7K030A06	3 x 6	1,04 - 26,42	700 - 1042	55
03200F7K040A06	4 x 6	1,125 - 28,58	837 - 1246	45
03200F7K050A06	5 x 6	1,185 - 30,1	979 - 1457	36
03200F7K030A04	3 x 4	1,315 - 28,83	902 - 1342	70
03200F7K040A04	4 x 4	1,255 - 31,88	1144 - 1702	60
03200F7K050A04	5 x 4	1,348 - 34,24	1320 - 1964	48
03200F7K020A02	3 x 2	1,305 - 33,15	1277 - 1900	95
03200F7K040A02	4 x 2	1,455 - 36,96	1639 - 2439	80
03200F7K050A02	5 x 2	1,556 - 39,52	1925 - 2439	64

Other dimensions and colors available on request.